


CAN850 QUICK START INSTRUCTIONS

INSTALLATION & START UP

- 1. Add water to the brine tank until it is 2" deep in the bottom of the tank. Do not add salt at this time. Turn off main water supply.
- Install unit as per local plumbing codes. (Refer to detail instructions on page 5 of operation manual) Avoid pinched o-rings during installation by applying (provided with install kit) NSF certified lubricant to all seals. Be sure to leave the unit in the "BYPASS" position.
- 3. Plug the power transformer into an approved power source. Connect the power cord to the valve.
- When power is supplied to the control, the screen may display "INITIALIZING WAIT PLEASE" while it finds the service position.
- 5. Press and hold the SET/REGEN button until you hear a beep to advance the valve to the BACKWASH position.
- 6. Open the inlet on the bypass valve slowly and allow water to enter the unit. (The outlet of the bypass should remain closed to prevent any fines or debris from entering the plumbing system) Allow all air to escape from the unit before turning the water on fully then allow water to run to drain for 3-4 minutes or until all media fines are washed out of the softener.
- 7. Press any button to advance to the BRINE position. Check the water level in the brine tank to insure the valve is drawing brine properly.
- 8. Press any button to advance to the RINSE position. Check the drain line flow. Allow the water to run for 3-4 minutes or until the water is clear.
- Press any button to advance to the REFILL position. Check that the valve is filling water into the brine tank. Allow the valve to refill for the correct amount of time as displayed on the screen to insure a proper brine solution for the next regeneration.
- 10. The valve will automatically advance to the service position. Open the outlet valve on the bypass. Add salt to brine tank.
- 11. Program unit.



PROGRAM INSTRUCTIONS

